## AMENDMENT TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

## Listing of Claims:

1. (currently amended) A hand hair dryer (1) comprising: an electric fan (2) and an electric heater (3), located in line with the electric fan for generating an air stream (4) from a barrel portion (5), in which the fan (2) is located in a housing portion (6) and the heater (3) is located inside the barrel portion (5), that on the housing portion (6), a first handle grip (8) that has operator control elements (7) is located at an angle of approximately 90° to the barrel portion (5), wherein

the barrel portion (5) is embodied as a second handle grip (9) and

a commonly actuatable cold air combination switch (16, 16.1, 16.2) is located between the first handle grip (8) and the second handle grip (9), and is configured to be actuated selectively from the first or second handle grip 8, 9, using by direct contact between the cold air combination switch and one finger of a hand on either the first handle grip (8) or the second handle grip (9).

- 2. (previously presented) The hand hair dryer in accordance with claim 1, wherein the second handle grip (9) is heat-insulated.
- (previously presented) The hand hair dryer in accordance with claim 1, wherein the barrel portion (5) is heat-insulated from the outside.
- 4. (previously presented) The hand hair dryer in accordance with claim 1, wherein the second handle grip (9) and the barrel portion (5) are embodied as heat-insulated from the outside.

- 5. (previously presented) The hand hair dryer in accordance with claim 1, wherein the second handle grip (9) is shaped cylindrically.
- 6. (previously presented) The hand hair dryer in accordance with claim 1, wherein the first and second handle grips (8, 9) are each provided with a nonslip surface (13).
- 7. (currently amended) The hand hair dryer in accordance with claim 1, wherein and further comprising a first cold air switch (10) is located on the first handle grip (8), and a second cold air switch (11) is located on the second handle grip (9).
- 8. (canceled)
- 9. (previously presented) The hand hair dryer in accordance with claim 1, wherein a pushbutton (17) is provided as the cold air combination switch (16).
- 10. (previously presented) The hand hair dryer in accordance with claim 1, wherein a one-leaged toggle switch (18) is provided as the cold air combination switch (16.1).
- 11. (previously presented) The hand hair dryer in accordance with claim 1, wherein two-legged toggle switch (19) is provided as the cold air combination switch (16.2).
- 12. (previously presented) The hand hair dryer in accordance with claim 1, wherein a centrally located warm-air conduit (28) and a coaxial cold-air conduit (29) are provided in the barrel portion (5), and the central warm-air conduit (28) is formed by a hollow-cylindrical barrel (30), in which the heater (3) is located; that the coaxial cold-air conduit (29) is formed by the barrel portion (5) and the central warm-air conduit (28); that the central warm-air conduit (28) and the coaxial cold-air conduit (29) are acted upon by a cold air stream (31) of the fan (2), and by means of the heater (3), a warm air stream outlet (32) is effected out of the central warm-air conduit (28), and a cold air stream (33) is effected from the coaxial cold-air conduit (29).

3 of 10